



晶体管光耦

Photo Transistor

**QX3H74**

宁波群芯微电子股份有限公司

NINGBO QUNXIN MICROELECTRONICS CO., LTD.

中国 浙江省宁波杭州湾新区玉海东路 68 号

68 Yuhaidong Road, Hangzhou Bay New District, Ningbo, Zhejiang, China

## 概述 Description

QX3H74是一款由发光二极管和光电晶体管组成的光电耦合器。十六引脚封装（SSOP16）。

The QX3H74 is a photoelectric coupler composed of light-emitting diode and phototransistor. It is packaged in a 16-pin package at SSOP16.

## 特性 Features

- 电流转换比(CTR)范围: 50%~600% ( $I_F=5\text{mA}$ ,  $V_{CE}=5\text{V}$ ,  $T_a=25^\circ\text{C}$ )  
Current transfer ratio: 50%~600% ( $I_F=5\text{mA}$ ,  $V_{CE}=5\text{V}$ ,  $T_a=25^\circ\text{C}$ )
- 输入-输出隔离电压 ( $V_{ISO}=3750\text{ Vrms}$ )  
High isolation voltage between input and output( $V_{ISO}=3750\text{ Vrms}$ )
- 集电极-发射极击穿电压  $BV_{CEO}\geq 80\text{V}$   
Collector - emitter breakdown voltage  $BV_{CEO}\geq 80\text{V}$
- 工作温度:  $-55^\circ\text{C}\sim+110^\circ\text{C}$   
Operating Temperature:  $-55^\circ\text{C}\sim+110^\circ\text{C}$
- 符合加强绝缘标准  
Meet reinforced insulation standards
- 符合安规标准: UL 1577, VDE DIN EN60747-5-5 (VDE 0884-5) , CQC11-471543-2022  
Meet safety standard approval: UL 1577, VDE DIN EN60747-5-5 (VDE 0884-5) , CQC11-471543-2022


## 应用 Applications

- DC-DC 转换器  
DC-DC converter
- 通讯设备  
Communications equipment
- 可编程控制器  
Programmable controller
- 信号传输  
Signal transmission

## 封装和原理图 Package and Schematic Diagram



SSOP16



Pin Configuration

- 1. Anode
- 2. Cathode
- 15. Emitter
- 16. Collector

## 产品型号命名规则 Order Code

### QX 3H74 - UN Y - W (V) (ZZ)

①      ②                      ③   ④      ⑤      ⑥      ⑦

① 公司代码 Company Code (QX: 群芯 Qunxin)

② 产品系列 Product Series (3H74: 3H74)

③ 框架类型 Lead Frame (Cu: 铜框架 Copper)

④ 树脂类型 Epoxy Type (H: 无卤 Halogen-free)


⑤ 封装形式 Package (S: SSOP)

⑥ 器件工作温度范围 Device Operating Temperature Range (特殊范围需填或者空白 Special Range need to be filled in or left blank)

⑦ 内部补充代码 Internal Supplementary Code (数字或者空白 Number or None)

## 印字信息 Marking Information

- 印字中“”为群芯品牌 LOGO  
“”denotes LOGO
- 印字中“Y”代表年份; A(2018),B(2019),C(2020).....  
“Y”denotes YEAR: A(2018), B(2019), C(2020).....
- 印字中“WW”代表周号  
“WW”denotes Week's number
- 印字中“N”代表星期几  
“N”denotes day of the week
- 印字中的“H”代表无卤  
“H”denotes Halogen-free



### 绝缘和安规信息 Insulation and Safety related specifications

| 项目<br>Item                            | 符号<br>Symbol | 数值<br>Value | 单位<br>Unit | 备注<br>Remark                                                                                               |
|---------------------------------------|--------------|-------------|------------|------------------------------------------------------------------------------------------------------------|
| 爬电距离<br>Creepage Distance             | L            | >5.0        | mm         | 从输入端到输出端，沿本体最短距离路径<br>Measured from input terminals to output terminals, shortest distance path along body |
| 电气间隙<br>Clearance Distance            | L            | >5.0        | mm         | 从输入端到输出端，通过空气的最短距离<br>Measured from input terminals to output terminals, shortest distance through air     |
| 绝缘距离<br>Insulation Thickness          | DTI          | >0.4        | mm         | 发射器和探测器之间的绝缘厚度<br>Insulation thickness between emitter and detector                                        |
| 峰值隔离电压<br>Peak Isolation Voltage      | $V_{IORM}$   | 600         | $V_{peak}$ | DIN/EN/IEC EN60747-5-5                                                                                     |
| 瞬态隔离电压<br>Transient isolation voltage | $V_{IOTM}$   | 5000        | $V_{peak}$ | DIN/EN/IEC EN60747-5-5                                                                                     |
| 隔离电压<br>Isolation Voltage             | $V_{iso}$    | > 3750      | $V_{rms}$  | For 1 min                                                                                                  |

### 极限参数 Absolute Maximum Ratings ( $T_a=25^{\circ}\text{C}$ )

| 参数<br>Parameter                |                                                           | 符号<br>Symbol | 额定值<br>Rating | 单位<br>Unit         |
|--------------------------------|-----------------------------------------------------------|--------------|---------------|--------------------|
| 发射端<br>Input                   | 正向电流<br>Forward Current                                   | $I_F$        | 50            | mA                 |
|                                | 反向电压<br>Reverse Voltage                                   | $V_R$        | 6             | V                  |
|                                | 正向峰值电流(1us , pulse)<br>Peak forward current (1us , pulse) | $I_{FP}$     | 1000          | mA                 |
|                                | 功耗<br>Power Dissipation                                   | $P_D$        | 70            | mW                 |
| 接收端<br>output                  | 集电极功耗<br>Collector Power Dissipation                      | $P_C$        | 150           | mW                 |
|                                | 集电极电流<br>Collector Current                                | $I_C$        | 50            | mA                 |
|                                | 集电极-发射极电压<br>Collector-Emitter Voltage                    | $V_{CEO}$    | 80            | V                  |
|                                | 发射极-集电极电压<br>Emitter-Collector Voltage                    | $V_{ECO}$    | 7             | V                  |
| 总功耗<br>Total Power Dissipation |                                                           | $P_{tot}$    | 200           | mW                 |
| 隔离电压<br>Isolation Voltage      |                                                           | $V_{iso}$    | 3750          | $V_{rms}$          |
| 工作温度<br>Operating Temperature  |                                                           | $T_{opr}$    | -55~+110      | $^{\circ}\text{C}$ |
| 存储温度<br>Storage Temperature    |                                                           | $T_{stg}$    | -55~+125      | $^{\circ}\text{C}$ |
| 焊接温度<br>Soldering Temperature  |                                                           | $T_{sol}$    | 260           | $^{\circ}\text{C}$ |

### 产品特性参数 Electro-optical Characteristics (Ta=25°C)

| 参数<br>Parameter                     |                                                     | 符号<br>Symbol  | 条件<br>Condition                                   | 最小<br>Min.         | 典型<br>Typ.         | 最大<br>Max. | 单位<br>Unit    |
|-------------------------------------|-----------------------------------------------------|---------------|---------------------------------------------------|--------------------|--------------------|------------|---------------|
| 发射端<br>Input                        | 正向电压<br>Forward Voltage                             | $V_F$         | $I_F=10\text{mA}$                                 | -                  | 1.2                | 1.6        | V             |
|                                     | 反向电压<br>Reverse Current                             | $I_R$         | $V_R=4\text{V}$                                   | -                  | -                  | 10         | $\mu\text{A}$ |
|                                     | 输入电容<br>Terminal Capacitance                        | $C_t$         | $V=0, f=1\text{kHz}$                              | -                  | 30                 | 250        | pF            |
| 接收端<br>Output                       | 集电极暗电流<br>Collector Dark Current                    | $I_{CEO}$     | $V_{CE}=20\text{V}$                               | -                  | -                  | 100        | nA            |
|                                     | 集电极-发射极击穿电压<br>Collector-Emitter Breakdown Voltage  | $BV_{CEO}$    | $I_C=0.1\text{mA}, I_F=0\text{mA}$                | 80                 | -                  | -          | V             |
|                                     | 发射极-集电极电压<br>Emitter-Collector Voltage              | $BV_{ECO}$    | $I_E=0.01\text{mA}, I_F=0\text{mA}$               | 7                  | -                  | -          | V             |
| 传输特性<br>Transfer<br>Characteristics | 电流传输比<br>Current Transfer Ratio                     | $CTR^*$       | $I_F=5\text{mA}, V_{CE}=5\text{V}$                | 50                 | -                  | 600        | %             |
|                                     | 集电极-发射极饱和压降<br>Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_F=10\text{mA}, I_C=1\text{mA}$                 | -                  | 0.1                | 0.2        | V             |
|                                     | 隔离电阻<br>Isolation Resistance                        | $R_{ISO}$     | DC500V, 40~60%R.H.                                | $5 \times 10^{10}$ | $1 \times 10^{11}$ | -          | $\Omega$      |
|                                     | 隔离电容<br>Isolation capacitance                       | $C_{ISO}$     | $V=0, f=1\text{MHz}$                              | -                  | 0.3                | 1.0        | pF            |
|                                     | 上升时间<br>Rise Time                                   | $T_r$         | $V_{CE}=2\text{V}, I_C=2\text{mA}, R_L=100\Omega$ | -                  | 5                  | 18         | $\mu\text{s}$ |
|                                     | 下降时间<br>Fall Time                                   | $T_f$         | $V_{CE}=2\text{V}, I_C=2\text{mA}, R_L=100\Omega$ | -                  | 3                  | 18         | $\mu\text{s}$ |

注\*: 电流传输比= $I_C/I_F \times 100\%$ 。

Note\*:  $CTR=I_C/I_F \times 100\%$ .

## 典型光电特性曲线 Typical Electro-Optical Characteristics Curves

Fig.1 Relative Current Transfer Ratio vs. Forward Current




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Collector Current vs. Collector-emitter Voltage




Fig.4 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.5 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.6 Collector Dark Current vs Ambient Temperature




Fig.7 Response Time vs. Load Resistance




Fig.8 Frequency Response




Fig.9 Collector-emitter Saturation Voltage vs Forward Current






Fig.10 Switching Time Test Circuit & Waveforms




## 外形尺寸 Outline Dimensions

SSOP16



单位 Unit: mm

## 建议焊盘布局 Recommended Pad Layout




单位 Unit: mm

注：上图为产品正视图。

Note: The picture above is the front view of the product.



## 回流焊温度曲线图 Solder Reflow Profile




| 项目<br>Item                                                                                    | 符号<br>Symbol | 最小值<br>Min. | 最大值<br>Max. | 单位<br>Unit                  |
|-----------------------------------------------------------------------------------------------|--------------|-------------|-------------|-----------------------------|
| 预热温度<br>Preheat Temperature                                                                   | $T_s$        | 150         | 200         | $^{\circ}\text{C}$          |
| 预热时间<br>Preheat Time                                                                          | $t_s$        | 60          | 120         | s                           |
| 升温速率<br>Ramp-Up Rate ( $T_L$ to $T_P$ )                                                       | -            | -           | 3           | $^{\circ}\text{C}/\text{s}$ |
| 液相线温度<br>Liquidus Temperature                                                                 | $T_L$        | 217         |             | $^{\circ}\text{C}$          |
| 时间高于 $T_L$<br>Time Above $T_L$                                                                | $t_L$        | 60          | 150         | s                           |
| 峰值温度<br>Peak Temperature                                                                      | $T_P$        | -           | 260         | $^{\circ}\text{C}$          |
| $T_c$ 在 $(T_P - 5)$ 和 $T_P$ 之间的时间<br>Time During Which $T_c$ Is Between $(T_P - 5)$ and $T_P$ | $t_p$        | -           | 30          | s                           |
| 降温速率<br>Ramp-down Rate ( $T_P$ to $T_L$ )                                                     | -            | -           | 6           | $^{\circ}\text{C}/\text{s}$ |

注 Note:

建议在所示的温度和时间条件下进行回流焊，最多不能超过三次；

Reflow soldering is recommended at the temperatures and times shown, no more than three times;

## 波峰焊温度曲线图 Wave Soldering Profile



## 手工烙铁焊接 Soldering with hand soldering iron

A. 手工烙铁焊仅用于产品返修或样品测试;

Hand soldering iron is only used for product rework or sample testing;

B. 手工烙铁焊要求: 温度  $360^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , 时间  $\leq 3\text{s}$ 。

Hand soldering iron requirements: Temperature:  $360^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , within 3s.


## 包装 Packing

### ■ 汇总表 Summary table

| 封装形式         | 包装方式                          | 盘数量               | 盒数量              | 箱数量                 | 静电袋规格                        | 盒规格               | 箱(双瓦楞)规格             | 备注                                                         |
|--------------|-------------------------------|-------------------|------------------|---------------------|------------------------------|-------------------|----------------------|------------------------------------------------------------|
| SSOP16       | 卷盘<br>( $\phi 330$ mm 蓝盘)     | 2000 只/盘          | 2 盘/盒            | 10 盒/箱              | 450*390*0.1mm                | 353*340*60mm      | 650.375.365mm        | 首端各空 50 个空格,<br>末端空 100                                    |
| Package Type | Packing Form                  | Quantity per Reel | Quantity per Box | Quantity per Carton | Antistatic Bag Specification | Box Specification | Carton Specification | Note                                                       |
| SSOP16       | Reel<br>( $\phi 330$ mm Blue) | 2000 pcs /reel    | 2 reels /box     | 10 boxes /ctn       | 450*390*0.1mm                | 353*340*60mm      | 650.375.365mm        | Leave 50 Spaces at the beginning and 100 Spaces at the end |

### ■ 编带包装 Tape & Reel

- 1) 每卷数量: 2000 只。  
Qty/reel: 2000 pcs.
- 2) 每箱数量: 40000 只。  
Qty/ctn: 40000 pcs.
- 3) 内包装: 每盒 2 盘。  
Inner packing: 2 reels/box.
- 4) 示意图 Schematic:



单位 Unit: mm

---

## 注意 Attention

- 群芯持续不断改进质量、可靠性、功能或设计，保留此文件更改的权利恕不另行通知。  
QUNXIN continuously improve quality, reliability, function and design. We reserve the right to change this document without prior notice.
- 请遵守产品规格书使用，群芯不对使用时不符合产品规格书条件而导致的质量问题负责。  
Please use in accordance with the product specification. QUNXIN is not responsible for the quality problems caused by non-compliance with the product specifications.
- 对于需要高可靠性或安全性的设备/装置需求，请联系我们的销售人员。  
For equipment/devices requiring high reliability or safety, please contact our sales representatives.
- 当需要用于任何“特定”应用时，请咨询我们的销售人员。  
When requiring a device for any “specific” application, please contact our sales in advice.
- 如对文件中表述的内容有疑问，欢迎联系我们。  
If you have any questions about the contents of the document, please contact us.